



CERTIS B4

Direct Thermal Printer

Enhance patient safety and clinical workflow. PDC Certis direct thermal printers offer easy integration, simple implementation and are best equipped for your full identification printing needs.

Reliable and robust printer backed by an industry leading 2-year warranty

Supports a variety of healthcare print applications including chart labels, medication labels, Mother/Baby wristbands and more

Compact, easy media loading design

Compatible with leading EMRs including Epic, Cerner, Meditech, and others.



Versatile print applications /
Fast printing in a compact form



CERTIS B4

Direct Thermal Printer

SPECIFICATIONS	
Part number	PDC4I-DT-PDA
Description	Direct thermal printer
Resolution	203 dpi
Printing method	Direct thermal
Print speed	15,2 cm/sec – up to 6 ips
Interface	<ul style="list-style-type: none">. USB 2.0 (full speed mode). Internal Ethernet (10/100 Mbps). RS-232 (serial port). USB host for scanner or PC keyboard
Printer language	ZPL, ZPL II, TSPL-EZTM
Bar codes	<ul style="list-style-type: none">. 1D bar code: Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, interleave 2/5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN et UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11. 2D bar code: PDF-417, Maxicode, DataMatrix, QR code, Aztec, MicroPDF417
Media type	Roll of wristbands & labels
Max. print width	10,8 cm (4.25")
Max. print length	2540 cm (1000")
Media length	1,9 ~ 11,4 cm (0,7" ~ 4,5")
Max. roll diameter	12,7 cm (5.0") OD
Core diameter	Core Size 2,5 cm (1") core or 3,8 cm (1,5") core
Media sensing	<ul style="list-style-type: none">. Gap transmission sensor. Black mark reflective sensor. Head open sensor
Dimensions	<ul style="list-style-type: none">. Millimeter: 172 mm (W) x 165 mm (H) x 195 mm (D). Inch: 6,77" (W) x 6,50" (H) x 7,68" (D)
One power switch, one feed button, one LED (3 colours)	Operation Switch, Button, LED
Environment Condition	<ul style="list-style-type: none">. Operation: 5 ~ 40°C, 25 ~ 85% non-condensing. Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety Regulation	FCC, UL, CE, NOM
Warranty	2 years
Included in box	External Power Supply, Power Cord, USB Cable, USB Drive with: Labeling Software, Quick Start Guide & User Manual installed



Contact your local Customer Service to learn more!

European Headquarters

Rue de l'Industrie, 17
1400 Nivelles - Belgium
+32 67 89 56 56
info@pdhealthcare.eu
www.pdhealthcare.eu

United-Kingdom

Units 6, 7 & 8, Dencora Business Centre,
Whitehouse Road, Ipswich
IP1 5LU
020 8614 8880
info@pdhealthcare.co.uk
www.pdhealthcare.co.uk